



**INTRATEC**  
100% SHOPPING

**Datasheet  
Main switch  
Art. No. MKDGH12-01**

**Intratec Warenhandels GmbH**

Gruetzmuehlenweg 46  
22339 Hamburg  
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: [info@intratec-hh.de](mailto:info@intratec-hh.de)

WEB: [www.intratec-shop.de](http://www.intratec-shop.de)



## Electrical specifications

Service voltage: 400V AC

For installation of devices up to max. 63A

Material enclosure: Acrylic ester styrene acrylonitrile (ASA)

Enclosure colour: Grey RAL 7035

Material door: Polycarbonate (PC)

Door colour: Transparent

Glow wire test: 650°C

Protection class: II / Protection rating: IP65

Temperature resistance: -25°C to +60°C

Manufactured according to DIN IEC60670 / IEC 60228

Halogen free, RoHS compliant, CE, UV stable

Optional lock with key (lockable door)

Pre-stamping for cable glands:

Up to 12 modules: M20, M25, M32

From 12 modules up to M40

With built-in DIN rail for all standardised circuit breakers / RCDs to DIN 43880

Finger-safe N/PE terminal strip

Fixing material (also UV-resistant, weatherproof and halogen-free)

Installation instructions

### Dimensions:

**A:** 259 mm

**B:** 319 mm

**C:** 144 mm

**E:** 210 mm

**F:** 130 mm

