



INTRATEC
100% SHOPPING

**Datasheet
Main switch
Art. No. JSNL002**

Intratec Warenhandels GmbH

Gruetzmuehlenweg 46
22339 Hamburg
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: info@intratec-hh.de

WEB: www.intratec-shop.de



Electrical Specifications Light

Incl. LED illuminant

Rated power: 3W

Operating voltage: 220-240V AC / 50-60Hz

Emergency light function: 3 hours

Incl. manual test function, incl. test button

Accumulator: Ni-Cd (CE marking)

Battery charging time: 24 hours

Battery life: 4 years

LED service life: 50,000 hours

60% energy saving compared to conventional lamps

Housing / Dimensions:

300x50x230mm

Material housing: shatterproof polycarbonate

Material lens: high quality polycarbonate

Protection Class: IP20

Mounting type: ceiling mounting / wall mounting

According to DIN EN 60598-2-22 and for installations according to DIN VDE 0108

Included in delivery: Emergency luminaire incl. Lamp, Operating instructions in German, 4 different information signs (self-adhesive emergency exit signs (pictograms) Rescue arrow down, Rescue arrow right, Rescue arrow left, Rescue arrow up)

