



**INTRATEC**  
100% SHOPPING

**Datasheet  
Main switch  
Art. No. MKHT2-01**

**Intratec Warenhandels GmbH**

Gruetzmuehlenweg 46  
22339 Hamburg  
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: [info@intratec-hh.de](mailto:info@intratec-hh.de)

WEB: [www.intratec-shop.de](http://www.intratec-shop.de)



## Electrical Specifications

Buttons quantity: 2

Buttons: Up/Down 1-stage

1: Up (1NO)

2: Down (1NO)

Buttons mechanically locked against each other

therm. Rated current: 10A

Rated voltage: 660V

max. Operating voltage: 400V

Temperature resistance: -operation: -25°C to +70°C; -storage: -40°C to +70°C

Lifetime: 3 million operations

Max. cable cross-section: 2x 1,5mm<sup>2</sup> or 1x 2,5mm<sup>2</sup>

Connections: finger-safe screw connection

Cable entry on top

Cable grommet included

Cable entry: 2-4 buttons: 12-17mm average, 6-12 buttons: 15-20mm average

Material: thermoplastic

Protection class: IP65 / Protection class: II / Marking: CE

harm. Regulations: EN60947-1, EN60947-5-1, EN60529, EN60204-1, EN60204-32, EN418, 2006/95 CE, 93/68 CE, 98/37 CE, 2004/108 CE

**Dimensions:**

A= 264mm

B= 166mm

C= 66mm

D= 77mm

weight: 0,28 kg

