



INTRATEC
100% SHOPPING

**Datasheet
Main switch
Art. No. JSNL007**

Intratec Warenhandels GmbH

Gruetzmuehlenweg 46
22339 Hamburg
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: info@intratec-hh.de

WEB: www.intratec-shop.de



Electrical Specifications Light

Frost-proof emergency luminaire for outdoor use down to -20°C

Rated power: 1,5W

Detection range: 24 metres

Operating voltage: 230 AC

Emergency light function: 3 hours

Automatic test function AUTOTEST, signalling via 3x colored LED, test button included

Test results with fault analysis (illuminant, charging and battery circuit) as well as status indication (operation, AUTOTEST) via 3x colored LED

Automatic function test (AUTOTEST type A) weekly

automatic duration test (AUTOTEST type B) every 3 months

Accumulator: Ni-Cd (CE marking)

Battery charging time: 24 hours

Battery life: 4 years

LED service life: 50,000 hours

60% energy saving compared to conventional lamps

Housing / Dimensions:

329x144x210mm

Material housing: shatterproof polycarbonate, impact-resistant, shatterproof, RAL 9003 (white)

Material lens: high-quality polycarbonate, transparent, impact-resistant, shatterproof

Permissible ambient temperature -20°C to 40°C

Protection class: IP65

Mounting type: ceiling mounting

According to DIN EN 60598-1, DIN EN 60598-2-22, DIN EN

62034 and DIN EN 1838 for systems according to DIN VDE 0108, for separate operation

The delivery programme includes: Emergency luminaire incl. Illuminant, Cover for two-sided application of pictograms, Operating instructions in German, 3 different information signs (Self-adhesive emergency exit signs (pictograms) Rescue arrow down, Rescue arrow right, Rescue arrow left)

