



INTRATEC
100% SHOPPING

**Datasheet
Main switch
Art. No. MKHT6-03**

Intratec Warenhandels GmbH

Gruetzmuehlenweg 46
22339 Hamburg
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: info@intratec-hh.de

WEB: www.intratec-shop.de



Electrical Specifications

Number of buttons: 6

1: Emergency stop (1NC)

2: Cap

3: Up (2NO stepped)

4: Down (2NO stepped)

5: Left (2NO stepped)

6: Right (2NO stepped)

Buttons mechanically locked against each other

therm. Rated current: 10A

Rated voltage: 660V

Max. Operating voltage: 400V

Temperature resistance: -operation: -25°C to +70°C; -storage: -40°C to +70°C

Lifetime: 3 million operations

Max. cable cross-section: 2x 1,5mm² or 1x 2,5mm²

Connections: finger-safe screw connection

Cable entry on top

Cable grommet included

Cable entry: 2-4 buttons: 12-17mm average, 6-12 buttons: 15-20mm average

Material: thermoplastic

Protection class: IP65 / Protection class: II / Marking: CE

harm. Regulations: EN60947-1, EN60947-5-1, EN60529, EN60204-1, EN60204-32, EN418, 2006/95 CE, 93/68 CE, 98/37 CE, 2004/108 CE

Dimensions:

A= 424mm

B= 310mm

C= 71mm

D= 82mm

weight: 0,59 kg

