



INTRATEC
100% SHOPPING

**Datasheet
Main switch
Art. No. JSNLBL04**

Intratec Warenhandels GmbH

Gruetzmuehlenweg 46
22339 Hamburg
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: info@intratec-hh.de

WEB: www.intratec-shop.de



Electrical Specifications

Material housing: polycarbonate, impact-resistant, unbreakable

Colour: RAL 9003 white

Material cover: polycarbonate, opal, impact resistant, shatterproof

Pictogram: PVC film, self-adhesive

Mounting type: wall and ceiling mounting

Protection class: IP54

Protection class: II

Light source: LED max. 1,2 W

Connected load: DS: max. 9VA

Connected load: BL: max. 4,4 VA

Battery: LiFePO4 3,2 V / 1,6 Ah

Emergency light: 3h and 8h (adjustable via jumper provided)

120 lm (mains operation) / 120 lm (emergency operation) 3 hours

120 lm (mains operation) / 50 lm (emergency operation) 8 hours

AUTOTEST

incl. pictogram set (emergency exit RW left, RW right, RW straight ahead)

EKW: 18 m

Dimensions:

A: 372 mm

B: 128 mm

C: 94 mm

D: 83 mm

