



**INTRATEC**  
100% SHOPPING

**Datasheet  
Main switch  
Art. No. MKAAGH24-T**

**Intratec Warenhandels GmbH**

Gruetzmuehlenweg 46  
22339 Hamburg  
Germany

FON: +49 40 538092 888

FAX: +49 40 538092 930

MAIL: [info@intratec-hh.de](mailto:info@intratec-hh.de)

WEB: [www.intratec-shop.de](http://www.intratec-shop.de)



## Electrical specifications

Service voltage: 400V AC

Material housing: acrylonitrile butadiene styrene (ABS)

Colour: White RAL 9003

Material door: Acrylonitrile butadiene styrene (ABS)

Colour: Transparent or white

For installation of devices up to max. 63A

With built-in DIN top-hat rail for all standard circuit breakers / residual current circuit breakers according to DIN 43880

Finger-safe N/PE terminal strip

Fixing material

Installation instructions

Protection class: II / Protection rating: IP40

Door hinge: right or left

Pre-stamping for cable glands: none

Glow wire test: 650°C

Temperature resistance: -25°C to +60°C

RoHS conform, CE

Manufactured according to DIN IEC60670 / IEC 60228

Optional lock with key

**Dimensions:**

**A:** 310 mm

**B:** 375 mm

**C:** 96 mm

**D:** 219 mm

**E:** 221,5 mm

